



Kest ProFlow Mixer

The best mixer we ever built for critical pharma and biotechnology applications.

DS-000012 EN REV B

Kest ProFlow Mixer

The Kest ProFlow Mixer line is a new generation of aseptic magnetic coupled mixers. With its state of the art mixing performance and ability to mix to the last drop, it is a perfect choice for critical pharma and biotech applications.

The Kest ProFlow range covers mixing volumes up to 1200 liters and is designed for CIP/SIP applications.

With our advanced Speed Sensor technology, you will have a reliable process control with real time monitoring.

The Drive Unit is fan-less and totally enclosed in a hygienic cover - perfectly adapted to a clean room environment.

The ProFlow DC motor has an efficiency >95% thanks to and advanced integrated control circuit. The Pro Flow will minimize energy consumption and save both money and environment.

The unique brushless DC motor eliminates the need of a frequency converter to control the motor speed.

The Kest ProFlow range can be customized to perfectly fit your needs. We offer a wide range of materials and retrofit options, please contact your reseller for a quote.

Kest Mixer range for various mixing applications

Kest has developed several product lines for various mixing applications and clean room needs. The KM product line was developed for a large volume range and the Rapid

Motion (RM) line for medium shear force generation. See separate data sheets on the other product lines in the Kest Mixer family or contact your reseller for more information.

We bring flow to your mixing process

Our mixers and components have one purpose: to make your mixing process flow. 24/7. To ensure predictable and compliant results. To minimize maintenance. To minimize waste. To minimize energy use. To maximize the value created by your mixing process.



✓ **Perfect mixing result**
After years of experience developing mixers this mixer will deliver a perfect mixing result over and over again.

✓ **ZERO particle shedding**
The robust bearing combination of Zirconium oxide and SiC and the fine-tuned geometry, ensures no particle generation. *

✓ **Sustainable**
The advanced motor boosts an impressive energy efficiency of >95%. While saving money, it also helps to reduce your carbon footprint significantly and due to low heat generation there is no need for compensating cooling - you can call it - Green Mixing.

✓ **Full integrity of the tank**
The magnetic coupling between the mixing head and drive unit ensures total integrity of the tank. All tank plates are FEM analyzed according to PED & ASME.

✓ **Enhance your workplace**
Due to the design of the drive unit it is extremely silent during operation enhancing the environment for the operators.

✓ **Mixing to the last drop**
The wings fixed position close to the tank bottom and the possibility to run the mixer during emptying of the tank, ensures full product recovery.

✓ **Cleanroom optimized**
The drive unit does not contain any fans that will interfere with your laminar air flow. It is totally capsuled in a smooth hygienic cover that is easy to keep clean.

✓ **Minimal heat transfer**
Thanks to the advanced drive unit, the energy is converted to rotation speed and a minimum result in heat. This prevents that heat is transferred into your application.


✓ **Integrated speed sensor**
The mixer is equipped with an integrated speed sensor that measures the speed of the mixing head, that the mixing head is in place and that it rotates in the right direction.

✓ **Minimize downtime**
The low weight of the drive unit and our patented Kest-Lock connection ensures quick disconnection from the tank plate during maintenance.



* The external test, according to USP<788> PARTICULATE MATTER IN INJECTIONS, could not detect any particles from the bearing.


General information




Mixing Head




Male Post



Tank Plate



Drive Unit



Power & logic box

The Kest ProFlow Mixer is a magnetically coupled mixer containing 4 modules, Mixing head, Male Post, Tank plate and Drive Unit.

To secure the integrity of the tank, the tank plate is welded into the tank, the mixing head and drive unit couples through the wall of the tank plate with magnetic forces. Welding tools and a welding guideline is available for easy and safe installation of the tank plate.

To select the appropriate model, use the selection guide in this data-sheet. For complex mixing applications contact your reseller for consultation.


The Power and Logic box contains the logic unit safely mounted in a cabinet. The box comes with size 20/70 and 70/120, the smaller units have the logic integrated in the drive unit.

Table of Content

| | |
|---------------------------|--------|
| We bring flow | Page 2 |
| General information | Page 3 |
| Dimensions | Page 4 |
| Specifications | Page 5 |
| Weights | Page 5 |
| Drive unit specifications | Page 6 |

| | |
|-------------------------|---------|
| Power & Logic box | Page 8 |
| SpeedSensor | Page 9 |
| Control Unit Mixer, CUM | Page 10 |
| Selection guide | Page 11 |
| Order information | Page 14 |


Dimensions



| SIZE | A mm [in] | B mm [in] | C mm [in] | D mm [in] | E mm [in] | F mm [in] | G mm [in] | H mm [in] |
|--------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| 0/3 | 155 [6.102] | 89 [3.504] | 6 [0.236] | 55 [2.165] | 7 [0.276] | 82 [3.228] | 33 [1.299] | 12 [0.472] |
| 3/7 | 225 [8.858] | 89 [3.504] | 6 [0.236] | 55 [2.165] | 7 [0.276] | 96 [3.780] | 46 [1.811] | 12 [0.472] |
| 7/20 | 241 [9.488] | 89 [3.504] | 6 [0.236] | 84 [3.307] | 7 [0.276] | 120 [4.724] | 56 [2.205] | 16 [0.630] |
| 20/70 | 275 [10.827] | 102 [4.016] | 7,94 [0.236] | 89 [3.504] | - [-] | 142 [5.591] | 71 [2.795] | 20 [0.787] |
| 70/120 | 282 [11.102] | 102 [4.016] | 8 [0.236] | 99 [3.898] | - [-] | 160 [6.299] | 71 [2.795] | 20 [0.787] |

Note! You can download 3D models of all our mixers from our CAD library at www.kest.se

Specifications



Mixing Head



Male Post



Tank Plate


MECHANICAL SPECIFICATIONS

| | Mixer head | Male post | Tank plate |
|-----------------------|---|------------------------|---------------------|
| Material grade | EN 1.4435/ASTM 316L, Silicone carbide (SiC) | Zirconium Oxide (ZrO2) | EN 1.4435/ASTM 316L |
| Material requirement | EN 10 272/10028-7, A479/A240 or SA479 SA240 | | |
| Documentation | Heat Certificate 3.1 acc. to EN 10 204 | | |
| Surface finish | Ra≤0.5 µm on surfaces in product contact, Mixer Head manually polished + electro polished | | |
| Design Temperature | [0°C to +150°C] [+32°F to +302°F] | | |
| Operating temperature | [0°C to +135°C] [+32°F to +275°F] | | |
| Design Pressure | [-1 bar(g) to + 7 bar(g)] [-14.5 psi to +101.5 psi] | | |
| pH range | 1-14 | | |
| Marking | Head and Bearing is marked with ID No. Tank plate is marked with material grade and heat number | | |
| Packing | Each item is sealed in vacuum plastic bag, labelled with article code and packed in a box | | |
| Male bearing sealing | EPDM, Silicone or Kalrez, approved acc. FDA regulation CFR 177.2600, USP Class VI | | |
| Quality Assurance | Each product is controlled and tested acc. to Kest Technology quality assurance system | | |

Weights

| SIZE | MIXING HEAD kg / [lb] | MALE POST kg / [lb] | TANK PLATE kg / [lb] | DRIVE UNIT* kg / [lb] | TOTAL* kg / [lb] |
|--------|--------------------------|------------------------|-------------------------|--------------------------|---------------------|
| 0/3 | 0.3 / [0.7] | 0.02 / [0.04] | 0.2 / [0.5] | 2.5 / [5.5] | 3.0 / [6.6] |
| 3/7 | 0.5 / [1.1] | 0.02 / [0.04] | 0.3 / [0.7] | 3.0 / [6.6] | 3.8 / [8.4] |
| 7/20 | 1.0 / [2.2] | 0.04 / [0.09] | 0.5 / [1.1] | 3.5 / [7.7] | 5.0 / [11.0] |
| 20/70 | 1.5 / [3.3] | 0.09 / [0.2] | 0.8 / [1.8] | 6.2 / [13.7] | 8.6 / [19.0] |
| 70/120 | 2.0 / [4.4] | 0.09 / [0.2] | 1.1 / [2.4] | 6.4 / [14.1] | 9.6 / [21.2] |

Drive unit specifications



| SIZE | MODEL | MOTOR POWER [W] | VOLTAGE DC [V] | CURRENT [A] | GEAR BOX RATIO [i] | SPEED RANGE [RPM] |
|--------|------------------|-----------------|----------------|-------------|--------------------|-------------------|
| 0/3 | KMPF-DU0/3A-0 | 63 | 24 | 3.5 | - | 50-680 |
| 3/7 | KMPF-DU3/7A-0 | 63 | 24 | 3.5 | 1:6 | 50-490 |
| 7/20 | KMPF-DU7/20A-0 | 63 | 24 | 3.5 | 1:6 | 50-490 |
| 20/70 | KMPF-DU20/70A-0 | 754 | 48 | 18 | 1:5 | 50-490 |
| 70/120 | KMPF-DU70/120A-0 | 754 | 48 | 18 | 1:5 | 50-490 |

DRIVE UNIT SPECIFICATIONS

| | |
|--------------------|--|
| Motor | Brushless DC |
| Design Temperature | [0°C to +40°C] [+32°F to +104°F] |
| Protection class | IP 65 |
| Capsulation | EN 1.4404, Ra < 0.8 µm, POM (bottom lid and Speed Sensor holder) |
| Cable | * (L) 3 meter multi wire, open cable end (see drive unit terminal connection configuration) |
| LED on housing | Green: Power, Yellow: Rotation, Blue: Pulse |
| Marking | Each item is marked with article code |
| Packing | Each item is sealed in plastic bag, labelled with article code and packed in a box |
| Quality Assurance | Each product is controlled and tested acc. to Kest Technology quality assurance system |

* Other lengths available on request

Power consumption

The Kest ProFlow mixer is equipped with a very efficient motor. The figures below is mean values based on operation in water (1 cP) with a standard mixing head and can vary depending on viscosity, mixing angle, volume and tank shape.

| SIZE | 50 RPM [W] | 100 RPM [W] | 200 RPM [W] | 300 RPM [W] | 400 RPM [W] | 490 RPM [W] |
|--------|---------------|----------------|----------------|----------------|----------------|----------------|
| 0/3 | 2.7 | 3.0 | 4.0 | 6.3 | 10.0 | 15.0 |
| 3/7 | 3.7 | 5.2 | 8.7 | 14.6 | 21.0 | 27.3 |
| 7/20 | 5.6 | 7.8 | 13.2 | 20.5 | 36.0 | 56.0 |
| 20/70 | 13.0 | 17.0 | 31.0 | 58.5 | 109.0 | 179.0 |
| 70/120 | 13.5 | 18.0 | 36.5 | 78.0 | 155.0 | 265.0 |

Terminal connection - Size 0/3, 3/7, 7/20

Drive unit, terminal connection (standard)

If you have chosen to run the mixer with the Kest control unit the wiring on the motor terminal needs to be changed according to table Drive unit, terminal connection (for Control Unit Mixer - CUM).

| TERMINAL ID | COLOUR / BASIC CONNECTION | DESCRIPTION | TYPICAL FUNCTION |
|-------------|---------------------------|---|--|
| X1:1 | Blue / Yes | Supply ground | - Ground |
| X1:2 | Brown / Yes | Logic supply voltage | + 24V DC |
| X2:1 | Purple / Yes | Logic ground | - Ground |
| X2:2 | Black / Yes | Control input C - hardware enable | + 24V DC closing switch (rotation start) |
| X3:1 | - | For CUM | For control unit |
| X3:2 | Pink / Yes | 0...10V - Speed control set value input | 0-10V variable speed control |
| X4:1 | Grey / If required | 10V DC output | 10V supply for speed control |
| X4:2 | White / If required | 0...10V - analogue speed value output | For converter or display |
| X5:1 | Red / Yes | Speed sensor pulse signal (PNP) | For pulse converter or display |
| X5:2 | Orange / If required | 24V PNP closing contact rotation indication | PLC |

Drive unit, terminal connection (for Control Unit Mixer - CUM)

| TERMINAL ID | COLOUR / BASIC CONNECTION | DESCRIPTION | TYPICAL FUNCTION |
|-------------|---------------------------|---|---|
| X1:1 | Blue / Yes | Supply ground | - Ground |
| X1:2 | Brown / Yes | Logic supply voltage | + 24VDC |
| X2:1 | Purple / Yes | Logic ground | - Ground |
| X2:2 | Black / Yes | Control input C - hardware enable | + 24VDC closing switch (rotation start) |
| X3:1 | Gray / Yes | For CUM | For control unit |
| X3:2 | Pink / Yes | 0...10V - Speed control set value input | 0-10V variable speed control |
| X4:1 | White / Yes | 10V DC output | 10V supply for speed control |
| X4:2 | - | 0...10V - analogue speed value output | For converter or display |
| X5:1 | Red / Yes | Speed sensor pulse signal (PNP) | For pulse converter or display |
| X5:2 | Orange / Yes | 24V PNP closing contact rotation indication | PLC |

Power & Logic box

The power & logic box for the 20/70 and 70/120 size is delivered with a 48V DC input as standard, this means you will supply the cabinet with 48V DC. As option we also have a version there you supply 110-230 V AC, in this optional version we provide an integrated AC to DC converter.

Power & Logic box - 48V DC input (standard)

| POWER & LOGIC BOX SPECIFICATIONS | |
|----------------------------------|--|
| Material | ABS |
| Design Temperature | [0°C to +40°C] [+32°F to +104°F] |
| Protection class | IP 66 |
| Measurement | 175 x 250 x 125 mm |
| Marking | Each item is marked with article code |
| Packing | Each item is sealed in plastic bag, labelled with article code and packed in a box |
| Quality Assurance | Each product is controlled and tested acc. to Kest Technology quality assurance system |

Power & Logic box connection terminal (standard)

| TERMINAL ID | TERMINAL | DESCRIPTION | TYPICAL FUNCTION |
|-------------|----------|---|--|
| X106:3 | P1 | Supply | + 48VDC |
| X106:2 | P1 | Supply | - 0VDC |
| ≡ | P1 | Ground | Supply ground |
| X5:2 | P4 | 24V PNP closing contact rotation indication | Output signal of rotation, Yellow LED. For PLC. |
| X5:1 | P4 | Speed sensor pulse signal (PNP) | Output signal Speed pulse, Blue LED. For pulse converter or display |
| X4:1 | P4 | 10V DC output | 10V supply for speed control, if required |
| X100:4 | P4 | 24V DC output | + 24VDC supply for closing switch (rotation start), if required |
| X100:5 | P4 | Ground | Logic ground |
| X100:7 | P4 | Control input C - hardware enable | + 24VDC closing switch (rotation start), electronic ON/OFF switch. Green LED |
| X100:11 | P4 | 0...10V - Speed control set value input | 0-10V variable speed control |
| X100:12 | P4 | Ground | Logic ground |

Power & Logic box - 110 - 230 V AC input (optional)

POWER & LOGIC BOX SPECIFICATIONS

| | |
|--------------------|--|
| Material | PC, Grey |
| Design Temperature | [0°C to +40°C] [+32°F to +104°F] |
| Protection class | IP 66 |
| Measurement | 255 x 360 x 152 mm |
| Marking | Each item is marked with article code |
| Packing | Each item is sealed in plastic bag, labelled with article code and packed in a box |
| Quality Assurance | Each product is controlled and tested acc. to Kest Technology quality assurance system |

Power & Logic box connection terminal - AC input (option)

| TERMINAL ID | TERMINAL | DESCRIPTION | TYPICAL FUNCTION |
|-------------|----------|---|---|
| AC/L | | Supply Phase | + 110-230 V AC |
| AC/N | | Supply Neutral | 0 V AC |
| ≡ | | Ground | Supply ground AC |
| X5:2 | P4 | 24V PNP closing contact rotation indication | Output signal of rotation, Yellow LED. For PLC. |
| X5:1 | P4 | Speed sensor pulse signal (PNP) | Output signal Speed pulse, Blue LED. For pulse converter or display |
| X4:1 | P4 | 10V DC output | 10V supply for speed control, if required |
| X100:1 | P4 | - | - |
| X100:2 | P4 | - | - |
| X100:3 | P4 | - | - |
| X100:4 | P4 | 24V DC output | + 24VDC supply for closing switch (rotation start), if required |
| X100:5 | P4 | Ground | Logic ground |
| X100:7 | P4 | Control input C - hardware enable | + 24VDC closing switch (rotation start), electronic ON/OFF switch |
| X100:8 | P4 | - | - |
| X100:9 | P4 | - | - |
| X100:10 | P4 | - | - |
| X100:11 | P4 | 0...10V - Speed control set value input | 0-10V variable speed control |
| X100:12 | P4 | Ground | Logic ground |

Speed Sensor

The Kest Mixer speed sensor unit is a integrated sensor system that enables secure verification of the actual rotation of the mixer head inside the tank.

An integrated function in the Kest Mixers speed sensor also verifies that the mixer head is in place in the tank and that it is rotating in the correct direction, "clockwise".

The unit consists of a sensor, that is located underneath the magnetic rotor, and a converter unit integrated in the drive unit circuit board.

The output signal from the sensor is 1 pulse/rotation as standard, 1 pulse/magnet can be delivered upon request.

For visual indication of the different functions, the speed sensor is connected to the LED's located on the drive unit enclosure:

- **Green LED: Power (steady light)**
- **Yellow LED: Rotation (steady light)**
- **Blue LED: Pulse (pulsing light)**

The sensor and cable are designed for +150°C to withstand the temperatures in the tank plate during sterilization.

| MECHANICAL SPECIFICATIONS | | |
|---------------------------|--|-------------------------|
| | Sensor holder | Cabling |
| Material grade | POM C | Teflon-FEP |
| Design Temperature | [0°C to +150°C] [+32°F to +302°F] | |
| Packing | The Speed sensor is installed on the drive unit before delivery | |
| Quality Assurance | Each product is controlled and tested acc. to Kest Technology quality assurance system | |
| Electrical Specifications | | |
| Type | Hall effect switch, PNP closing circuit | |
| Voltage | 8-30 V DC | |
| Rated Current | 200 mA | |
| Model | Standard pulse | Max pulses (on request) |
| KMPF-0/3 | 1 pulse / rotation | 2 pulses / rotation |
| KMPF-3/7 | 1 pulse / rotation | 3 pulses / rotation |
| KMPF-7/20 | 1 pulse / rotation | 3 pulses / rotation |
| KMPF-20/70 | 1 pulse / rotation | 4 pulses / rotation |
| KMPF-70/120 | 1 pulse / rotation | 5 pulses / rotation |

Control Unit Mixer, CUM (optional)

The Kest control unit is developed for the smaller DC drive units to control and monitor the rotation speed of the mixer.


The Kest control unit is powered with 100-240 VAC at 50-60Hz that is transformed to 24 VDC, feeding the mixer.

The three pre-set buttons is used as quick buttons to set a certain speed value, each can be programmed to a specific RPM.

The unit is pre-programmed with ramping parameters for acceleration and deceleration to prevent the mixer from damage.

The display shows the rotation speed of the mixer and the target speed value. The display is also used when programming the pre-set buttons and for delivering error messages.

If you forgot to mount the mixing head in the tank it will show an error message.







SPECIFICATIONS


| Cabinet | |
|---------------------------|---|
| Material grade | Grey ABS |
| Measurement (HxWxD) mm | 24 VDC: 175 x 125 x 75 mm [6.890 x 4.921 x 2.953 in] 48 VDC: 360 x 255 x 152 mm [6.890 x 4.921 x 2.953 in] |
| Design Temperature | [0°C to +40°C] [+32°F to +104°F] |
| Packing | Each item is sealed in plastic bag, labelled with article code and packed in a box |
| Quality Assurance | Each product is controlled and tested acc. to Kest Technology quality assurance system |
| Electrical Specifications | |
| Power supply | 100 - 240 VAC / 50-60 Hz |
| Effect | 30 W, 100 W & 750 W |
| Protection class | IP66 |

Selection guide

The mixer is selected after volume and desired mixing type based on the viscosity of the media. The different mixer sizes are targeting a specific volume range based on viscosity of 1 cP. Depending on the viscosity you might need to go for a larger size even if you are in the target volume. The characteristics of the General, Gentle and Vigorous mixing is subjective and built on experience. See example in the end of the selection guide on how to select correct mixer size.







Example:

You want to select a mixer that shall generate General mixing

The max mixing volume is 30 liters

The viscosity of the media is 100 cP.

Size 0/3 has the range of 0-30 liter at 1 cP, but since the viscosity is 100 cP the capacity for General mixing is decreased to around 15 liters, see 0/3 graph at 100cP, orange line.

The next size is 3/7 with a range of 30-70 liter at 1 cP. That mixer can handle 34 liters of media at viscosity 100 cP, see 3/7 graph at 100cP, orange line.

For this application you need size 3/7.

For higher viscosities you might need to go up several sizes to find a mixer with the sufficient volume capacity.

Test centre

Mixing can be simple and complex, this selection guide sizes the mixer to the correct capacity. Mixing performance can be affected by many different factors, if you need support with your mixing application, we have long experience and an in-house fully equipped test centre. Do not hesitate to contact us with your mixing application.

Kest Mixer ProFlow (KMPF), Ref.No list

| SIZE | MIXING HEAD | MALE POST | TANK PLATE | DRIVE UNIT | MULTICABLE* |
|--------|-------------|-----------|------------|------------|-------------|
| 0/3 | 102440 | 100562 | 100383 | 102691 | 101290 |
| 3/7 | 102441 | 100562 | 100625 | 102692 | 101290 |
| 7/20 | 102442 | 101530 | 100647 | 102963 | 101290 |
| 20/70 | 102443 | 100415 | 100396 | 102673 | 102694 |
| 70/120 | 102444 | 100415 | 102629 | 102674 | 102694 |

*The multicable article is setup as 1 meter (3.3 ft), when ordering you specify the length of the cable you need by adding articles. If you order 3 articles you will get a 3 meter cable. For the 20/70 and the 70/120 the cable length specified is between the motor and the power and logic box. If you don't specify anything your mixer will be shipped with the standard cable length, see drive unit specification.

Kest Mixer ProFlow (KMPF), options - Ref.No list

| SIZE | POWER & LOGIC BOX 110-230V AC | CONTROL CABINET | ATTRACTOR* | MULTI TOOL* | WELDING TOOL |
|--------|----------------------------------|-----------------|------------|-------------|--------------|
| 0/3 | - | 100669 | 101620 | 101006 | 100446 |
| 3/7 | - | 100669 | 101620 | 101006 | 100923 |
| 7/20 | - | 102373 | 101436 | 101342 | 100802 |
| 20/70 | 102971 | 102904 | 100571 | 100655 | 100802 |
| 70/120 | 102971 | 102904 | - | 100655 | 100780 |

*See separate data sheet



kest