



- 1 Hexagonal socket bolt with fine pitch thread
- 2 Guiding plate
- 3 Threaded plate
- 4 Housing
- 5 Grip ring insert (hardened)

The claw which resists high tensile loads

Axial restraint safety claw for use with pressurized pump lines in lifting systems as well as for rainwater sewage lines that are at risk of undergoing back pressures, but only in combination with the NORMACONNECT® DCS RAPID standard connectors. The powerful add-on claw for non-pull-out resistant connections.

Materials

W1	W2	W3	W4	W5
x				

W1

- Material, Housing: Steel, surface protected
- Material, Closure unit: Steel, surface protected

Advantages at a glance

- ✓ Two parts (halves) with hardened grip ring inserts
- ✓ Strong guiding plates with threaded holes plus four hexagonal socket bolts with fine pitch thread

Technical data & Ordering information

NORMACONNECT® DCS RECORD CLAW								
Designation	DN	A (mm)	D (mm)	L (mm)	Torque (Nm)	Bolt (mm)	P max (bar)	W1 Product No.
RECORD Claw DN 50	50	21	75	69	12-15	M 8	up to 10	0262 1265 050
RECORD Claw DN 70	70	21	95	69	12-15	M 8	up to 10	0262 1266 070
RECORD Claw DN 80	75/80	21	100	69	12-15	M 8	up to 10	0262 1287 080
RECORD Claw DN 100	100	25	135	87	25-30	M 10	up to 10	0262 1246 100
RECORD Claw DN 125	125	25	160	95	30-35	M 10	up to 5	0262 1267 125
RECORD Claw DN 150	150	25	185	95	30-35	M 10	up to 5	0262 1268 150
RECORD Claw DN 200	200	30	235	111	60-65	M 12	up to 3	0262 1269 200

